



SPECIFICATIONS

1. ALUMINIUM FRAME W/FLASHING
2. STAINLESS STEEL PINTLE HINGE
3. 15 x 50mm EPDM GASKET (ALL ROUND COVER)
4. ALUMINIUM COVER GAUGE
5. ALUMINIUM COVER LINER
6. LIFTING MECHANISM WITH METAL TUBES AND COMPRESSION SPRINGS
7. ARM GUIDE BRACKET
8. 25mm THICK FIBERGLASS COVER INSULATION
9. HOLD OPEN ARM W/ METAL GRIP
10. LOCK STRIKE & PADLOCK HASP
11. STAINLESS STEEL ANCHOR TABS (QTY & LOCATION VARIES W/SIZE)
12. MS FOLDABLE HOLDING POST (L = 760MM)
13. MS HANDRAIL
14. SLAM LATCH



+6012 - 392 8447

salesbronteattic@gmail.com

bronteattic.my | BRONTÉ ATTIC (M) SDN BHD

bronteattic.sg | BRONTÉ ATTIC MARKETING

thaibronteattic.com | BRONTÉ ATTIC (THAILAND) CO., LTD

ROOF HATCH

MODEL

RHA 1010

(STANDARD SHOPDRAWING)

INSPECTION MAINTENANCE

Visual inspection for any damage or loose fixings must be done periodically and prior to use. No certified maintenance is required. Basic wear and tear preventative maintenance is recommended as per manufacturer, specifications recommendations.